



Drive**Tone Pro**

P/N:DT-A24V-xxx-RLG

RGBWW 24VDC Smart LED Driver

RGB, Tunable White & Dimming Control







The DriveTone Pro enables RGB, Tunable White & Dimming in one smart Driver. Eliminating the need for expensive and complex DMX systems. Each LED Driver controls a zone using the SmartAir app/voice control. In addition to the App, the system offers a traditional point of control using the DimTone Wall Switch (optional).







Enclosure Details

Dimensions	9.1"x 2.80" x1.94"	11.41"x 2.80" x1.94"	
Material	Sheet Metal		
Finish	Gray Matte Powder Coat		
Enviromental Rating	IP	23	



Features & Benefits

- Smart RGB, Tunable White, and Dimming Control in One Driver
- SmartAir App / Voice Control
- Eliminating the need for Expensive and Complex DMX Installations
- Works With AmbienTech's Smart Wall Switches (Optional)
- Complies to IEEE and Title 24 Flicker Requirements
- Superior Dimming Flicker Free to 0.1% before total Darkness
- Wiring Compartments With Knock-Outs for Safe and Easy Installation
- UL Listed
- Small Linear Form-Factor
- Current Limit Overload Protection
- Can be Loaded to Max Power with no Derating needed



Tel: *347-334-6368*



SPECIFICATIONS

\mathcal{C}	la	50	:2	

P/N		DT-A24V-96-RLG	DT-A24V-150-RLG	DT-A24V-200-RLG
Case	Туре	АВ		В
Output	Max Power	96W	150W	200W
	Rated Current	4A	6.5A	8A
	Rated Voltage	24VDC		
Input	Input Voltage	120-277VAC +/- 10%		
	Input Frequency	50/60Hz		
Protection	Over Current	Hiccup mode, auto-recovery after short circuit removed		
	Short Circuit			
	Over Temperature	90°C Max - Auto Recovery		
Environmental	Ambient Operating Temp	-30°C - + 40°C / -86°F - + 104°F		
	IP Rating	IP65		


Control Performance

Control Protocol	RGB / Tunable White / Dimming	
Dimming Range	0.1 - 100%	
Dim-to-Off	Yes	
Dimming Method	PWM (2400Hz)	
Dimming Curve	Logarithmic (Default)	

Flicker Performance Graph


As defined in IEEE P1789, the results are presented with the low-risk in yellow and no observable effect in green.

Complies to Title 24 Flicker Requirements.




WIRING

OVERVIEW



Mechanical Specifications



SYSTEM

FUNCTIONALITY



Add a point of control anywhere



Multi- color control



Grouping



Scalable & Versatile



Scheduling



No hub Needed



Cloud user management



Scenes



Biorhythm

SMARTHOME

INTEGRATION



Login Zone Grouping Dim-to-Warm

RGBWW

Dimming Only

BioRhythm

Scenes









Download the SmartAir App



WWW.AMBIENTECHINC.COM

Brooklyn Navy Yard 63 Flushing Avenue Brooklyn, NY 11205

P: 347-334-6368

E: Sales@ambientechinc.com