

Tunable White & Dimming Control System

The Cyan Wall Switch uses a standard end-to-end wiring configuration that eliminates the need for extra wires and resolves compatibility concerns.

This device offers a wide range of features, including over 16 million colors, adjustable white light, and the ability to be controlled through voice commands or an App.



RGB Mode



Tunable White


 Dimmable
0-100%


IT'S AS SIMPLE AS THAT.


 Automatic
Pairing by Turning
On the Switch

 Up to
700W


Multi Gang 3way


 Wire Free Unlimited
Load Capacity

Features & Benefits

- RGB Control
- TW Control
- SmartAir - App / Voice Control
- 3 Way Wireless / HardWire
- Dim-to-Off
- Flicker-Free Soft Dimming - Down to 0.1%
- 120VAC Wall Switch with No Battery Required
- UL Listed
- A Single Wall Switch Can Control Multiple LED Drivers
- Simple Installation - no Extra Wiring
- Fits US Standard Multi Gang Box
- Complies to IEEE and Title 24 Flicker Requirements
- No Compatibility Issues
- Classic Design to Match Existing Style Switches
- Fast Delivery – Shipping out of NY



Ordering Part Number Example:

P/N: CyanDim-WSx-SA X

Model Color

Colors


W
White

G
Grey

O
Ivory

B
Black


C
Almond

H
Hot


Compatible LEDS

The *TONES* system is compatible with any Constant Voltage Tunable White 12/24VDC LED fixture.


Track Light




Hanging Light Fixture



Downlight



User Interface



Specification Submittal


Project Name:	Company Name:
Project Number:	Contact Name:
Part Number:	Email:

Wiring


Overview

Option 1 Cyan RGBCW Installation

- Wired Connection
- - - Wireless Connection



Option 2 SleekTone CV Installation



Power & Ratings

Input	120-277 VAC ~ 50/60Hz
Max Load Hardwired	700W
Max Load Nonwired	Unlimited

Compliance

UL Listed	UL1472 / CSA C22.2 184.1
FCC	Class B Part 15


Environmental

Ambient Operating Temp	-30 °C - + 40 °C / -86°F - + 104°F
------------------------	------------------------------------

Dimming Performance

Control Protocol	RF / WIFI
Dimming Range	0.1 - 100%
Dim to Off	Yes
Dimming Method	PWM (2400Hz)

Mechanical Specifications




Note: Requires a U.S. wallbox 2in (64 mm) deep minimum.

Material	PC/ABS - 5VA Rating
Finish	White Glossy (Default)

System

Functionality



Smart Home

Integration



Download the SmartAir App



WWW.AMBIENTECHINC.COM

Brooklyn Navy Yard
63 Flushing Avenue
Brooklyn, NY 11205

P: 347-334-6368
E: Sales@ambientechinc.com